

Hole Digging Equipment Hand Held



FEATURES

- Power-GRIP™ operator handle
- Auger-LOK™ for stuck auger removal
- Honda GX35 all-position engine
- All metal centrifugal clutch
- Precision, spur gear transmission
- 1 inch diameter auger drive connection
- Magura® twist grip throttle control

242H EPIC™ SERIES ONE MAN HOLE DIGGER

The 242H EPIC™ Series hand-held Hole Digger features an all position, 4 Stroke engine. No more mixing oil with gas. No more separate fuel cans. And, no more smoky, exhaust with a Honda engine that meets current EPA emission standards. The 242H is built with professional features that make it ideal for both contractors and homeowners alike. Performance to dig up to an 8 inch (203 mm) diameter hole in a variety of soil classifications. Built with oversized ball bearings, heat treated shafts and precise, machine-cut gears designed to deliver long service life and high ROI. The unique, ergonomically engineered Power-GRIP™ operator handle helps maximize control, strength and balance plus, dampens vibration and reduces the effects of kickback and body fatigue while increasing overall digging comfort, productivity and jobsite safety. The 242H is also equipped with the convenient Auger-LOK™ for removing stuck augers. For use with the 2350 Series earth augers and auger extension.

SPECIFICATIONS

Engine	1.3 HP (1000 W) Honda GX35, all-position, 4 Stroke
Starter	Hand rewind
Fuel	Gasoline, unleaded, automotive grade
Transmission	Totally enclosed, spur gear, grease lubricated
Maximum Digging Torque	51 ft lbs (64 N.m)
Nominal Auger Rotation Speed	166 RPM, no load
Auger Drive Connection	1 inch (25.4 mm) round
Available Auger Diameter Range	2 inch (51 mm) to 8 inch (203 mm)
Standard Auger Digging Length	30 inch (762 mm)
Available Auger Extension	15 inch (381 mm), plain-tube type
Weight (less auger)	28 lbs (13 kg)



All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF10121901_v1.0

Hole Digging Equipment Hand Held



FEATURES

- Power-FLEX™ operator handles
- Auger-LOK™ for stuck auger removal
- Honda GCV160 engine
- All metal centrifugal clutch
- Precision, spur gear transmission
- 1 inch diameter auger drive connection
- Magura® twist grip throttle control

262H EPIC™ SERIES TWO MAN HOLE DIGGER

The 262H EPIC™ Series hand-held Hole Digger offers an uncompromising balance of power, performance and utility in a lightweight, two-man Hole Digger. Its Honda engine directly mounts to a totally enclosed, oil-lubricated transmission for maximum efficiency and is equipped with the convenient Auger-LOK™ for removing stuck augers. Inside, a high capacity, all-metal centrifugal clutch delivers maximum digging power and consistent performance over an extended service life. The exclusive Power-FLEX™ ergonomically engineered composite operator handles maximize control, strength and balance while helping to dampen vibrations. The effects of kickback and fatigue are reduced while increasing overall digging comfort, productivity and jobsite safety. The smooth operating, 4-stroke engine meets applicable emission and noise standards and provides the competitive edge when tackling the tough demands of both industrial and construction related hole digging projects. The 262H Hole Digger is ideally suited for both the home owner and small contractor alike. For use with the 2350 Series earth augers and auger extension.

SPECIFICATIONS

Engine	4.4 HP (3.3 Kw), Honda GCV160, 4 Stroke
Starter	Hand rewind
Fuel	Gasoline, unleaded, automotive grade
Transmission	Totally enclosed, spur gear, oil lubricated
Maximum Digging Torque	134 ft lbs (182 N.m)
Nominal Auger Rotation Speed	162 RPM, no load
Auger Drive Connection	1 inch (25.4 mm) round
Available Auger Diameter Range	2 inch (51 mm) to 12 inch (305 mm)
Standard Auger Digging Length	30 inch (762 mm)
Available Auger Extension	15 inch (381 mm), plain-tube type
Weight (less auger)	50 lbs (23 kg)

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF10121902_v1.0

Hole Digging Equipment Hand Held



FEATURES

- Power-FLEX™ operator handles
- Auger-LOK™ for stuck auger removal
- Honda GXV160 engine
- All metal centrifugal clutch
- Precision, spur gear transmission
- 1-3/8 inch hexagon auger drive connection
- Magura® twist grip throttle control

332H EPIC™ SERIES TWO MAN HOLE DIGGER

The 332H EPIC™ Series hand-held Hole Digger is designed to tackle a wide range of construction related hole digging projects...from simple backyard fencing to complex landscaping and soil sampling. Each is built with a time-proven transmission that includes oversized bearings, heat treated shafts and precision, machine cut gears that has created an industry wide reputation for delivering long service life and exceptional ROI. All with the power and performance to dig up to 18 inch (457 mm) diameter holes in a wide variety of soil classifications. When an auger becomes stuck use the convenient Auger-LOK™ to remove it. The exclusive Power-FLEX™ ergonomically engineered composite operator handles maximize control, strength and balance while helping to dampen vibrations. The effects of kickback and fatigue are reduced while increasing overall digging comfort, productivity and jobsite safety. For use with the 4400 Series earth augers and 5500 Series auger extensions.

SPECIFICATIONS

Engine	5.5 HP (4.1 Kw) Honda GXV160, 4-stroke
Starter	Hand rewind
Fuel	Gasoline, unleaded, automotive grade
Transmission	Totally enclosed, spur gear, oil lubricated
Maximum Digging Torque	190 ft lbs (225 N.m)
Nominal Auger Rotation Speed	144 RPM, no load
Auger Drive Connection	1-3/8 inch (35 mm) hexagon
Available Auger Diameter Range	2 inch (51 mm) to 18 inch (457 mm)
Standard Auger Digging Length	36 inch (914 mm)
Available Auger Extensions	15 inch (381 mm), plain-tube type. 36 inch (914 mm), continuous flighted.
Weight (less auger)	71 lbs (32 kg)



All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF10121903_v1.0

Hole Digging Equipment Hand Held



FEATURES

- Power-FLEX™ operator handles
- Auger-LOK™ for stuck auger removal
- Honda GXV160 engine
- All metal centrifugal clutch
- Precision, spur gear transmission
- 7/8 inch square auger drive connection
- Magura® twist grip throttle control

348H EPIC™ SERIES TWO MAN HOLE DIGGER

The 348H EPIC™ Series hand-held Hole Digger is designed to tackle a wide range of construction related hole digging projects...from simple backyard fencing to complex landscaping and soil sampling. Each is built with a time-proven transmission that includes oversized bearings, heat treated shafts and precision, machine cut gears that has created an industry wide reputation for delivering long service life and exceptional ROI. All with the power and performance to dig up to 18 inch diameter (457 mm) diameter holes in a wide variety of soil classifications. When an auger becomes stuck use the convenient Auger-LOK™ to remove it. The exclusive Power-FLEX™ ergonomically engineered composite operator handles maximize control, strength and balance while helping to dampen vibrations. The effects of kickback and fatigue are reduced while increasing overall digging comfort, productivity and jobsite safety. For use with PSD/PLD Series earth augers and auger extension.

SPECIFICATIONS

Engine	5.5 HP (4.1 kw) Honda GXV160, 4-stroke
Starter	Hand rewind
Fuel	Gasoline, unleaded, automotive grade
Transmission	Totally enclosed, spur gear, oil lubricated
Maximum Diggng Torque	190 ft lbs (225 N.m)
Nominal Auger Rotation Speed	144 RPM, no load
Auger Drive Connection	7/8 inch (22 mm) square
Available Auger Diameter Range	2 inch (51 mm) to 18 inch (457 mm)
Standard Auger Digging Length	36 inch (914 mm)
Available Auger Extension	15 inch (381 mm), plain-tube type
Weight (less auger)	71 lbs (32 kg)



All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF10121904_v1.0