

Surface Preparation Equipment Floor Strippers



FEATURES

- 10 inch maximum cutting blade width
- 3-bolt blade clamping system
- Adjustable height, folding operator handle
- Back-Saver™ Blade Angle Control System
- Central lubrication system
- Integral front lift handle
- Integral, concealed static weights
- Integral, non-slip push pad
- Magnetic-type ON/OFF switch
- 37 foot extension cord w/GFCI

FCS16GEN3 RIP-R-STRIPPER® FLOOR COVERING STRIPPER

The FCS Series RIP-R-STRIPPERS have revolutionized the industry with their innovative design and operational features. Quickly remove VCT tiles, rubber-backed carpeting and sheet type coverings from wood and concrete surfaces. Adjust blade attack angle without stopping work using the Back-Saver Blade Angle Control System for maximum productivity. The three screw blade clamping system prevents unwanted flooring material build ups further improving long term maintenance costs. Integral, 16 lb static weights eliminate maintenance and chance for lost parts. Adjustable operator handle with passive release feature easily folds for compact transport. Direct-drive, random orbit action. Welded, unitized frame. Blades interchange with FCS10GEN2 RIP-R-STRIPPER. Includes 1 each, part number FCS16-1100, 4 x 6 inch straight blade and 1 each part number FCS16-1300, 3 x 10 inch straight blade. For use in non-hazardous environments.

SPECIFICATIONS

Power Source	.75 HP (.56 Kw), 115 VAC, 60 HZ, 15.0 ampere, electric motor
Nominal Oscillations	1725/minute
Frame	Unitized, welded, steel plate
Bearings	Ball-type
Blade Drive System	Direct mount to orbital plate & motor
Extension Cord	12-3, SJTW x 37.0 ft (11.3 M) L, w/GFCI
Product Dimensions (L x W x H)	Length, operator handle extended, less blade: 39.5 inches (1003.3 mm) Width, base unit @ caster wheels: 14.1 inches (358.1 mm) Width, base unit @ orbital plate, less blade: 10.4 inches (264.2 mm) Width, operator handle: 23.1 inches (586.7 mm) Height, operator handle extended: 37.0 inch (939.8 mm) Length, operator handle folded/retracted, less blade: 24.4 inches (619.8 mm) Height, operator handle folded/retracted: 29.1 inches (739.1 mm)
Product Weight	137.2 lbs (62.2 kg), less blade & extension cord

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF13021201_v1.5