































SP8 SURFACE PLANER DRUM/FLAIL CONFIGURATION APPLICATION GUIDE



DRUM/FLAIL CONFIGURATION	FLAIL TYPE USED	REMOVING EXCESS CONCRETE OR ASPHALT MATERIALS	REMOVING TRAFFIC LINES	REMOVING SURFACE COATINGS	PROFILING SURFACES FOR NEW COATING APPLICATIONS	REQUIREMENTS	COMMENTS
 Star Flail	 SP8-3000					SP8-6000 Kit 124 flails 120 washers	Application: Remove coating materials while minimizing damage to cap surface. Finish: Smooth to medium. Service Life: 7-10 hours. Dimensions: 1C/v inch OD x B/, inch ID x Z/, inch thickness.
 Beam Flail	 SP8-3100					SP8-6100 Kit 124 flails 120 washers	Application: Light to medium duty asphalt/concrete removal. Finish: Medium to rough. Service Life: 7-10 hours. Dimensions: 1C/v inch OD x B/, inch ID x Z/, inch thickness.
 Tungsten Carbide Tipped Flail	 SP8-3200					SP8-6200 Kit 84 flails 84 washers	Application: Heavy duty asphalt/concrete removal. Finish: Rough, broom swept. Service Life: Up to 250 hours. Dimensions: 1C/v inch OD x B/, inch ID x Z/v inch thickness.
 Beam Traffic Line Removal	 SP8-3100					SP8-6105 Kit 184 flails 56 washers	Application: Medium duty paint and plastic traffic line removal from asphalt and concrete surfaces. Up cut or down cut flail direction. Finish: Smooth to medium texture finish. Service Life: Up to 10 hours. Dimensions: 1C/v inch OD x B/, inch ID x Z/, inch thickness.
 Milling/Traffic Line Removal	 SP8-3300					SP8-6300 Kit 28 flails 48 washers	Application: Remove paint and plastic traffic lines from asphalt and concrete surfaces. Not intended to penetrate surfaces. Pull machine toward operator for up cut flail rotation direction ONLY. Finish: Smooth texture finish. Service Life: Up to 30 hours. Dimensions: 1B/, inch OD x B/, inch ID x ZC/zn inch thickness.



Preferred method to produce maximum performance or productivity rates for most job applications.



Acceptable performance or productivity rates for most job applications.



Limited performance or productivity rates for most job applications.

www.generalequip.com