



FEATURES

- Omnitrix™ single matrix formulation for simplicity
- Extended segment height for longer service life
- Directionally marked for longer segment life
- Low acquisition cost

SG24-2300 DIAM-A-TACH™ DIAMOND SEGMENT GRINDING SYSTEM

The SG24-2300 DIAM-A-TACH Diamond Segment Grinding System offers an innovative solution for a wide variety of surface preparation job applications. The Omnitrix formulation allows the same matrix to be used on green concrete, high tensile epoxies, thin-film type floor coatings and fully cured concrete. Delivers balanced material removal rates and service life. This unique feature simplifies the proper matrix selection process and minimizes inventory stocking levels.

The rectangular-shaped, diamond segments have significantly greater thickness and height when compared to competitive products. This provides greater surface grinding area per unit and delivers substantially longer service life and higher ROI. The housing is directional marked for proper orientation to eliminate the top layer of tails from being inadvertently removed. Secures tight with a plastic wedge.

Use the SG24-2300 DIAM-A-TACH Grinding System with General SG12 and SG24 Legacy Series Surface Grinders and popular models of competitive single and dual head surface grinders.

SPECIFICATIONS

Segments Per Unit	4
Segment Grit/Bond Combination	Omnitrix: 30/40
Grinding Area Per DIAM-A-TACH Unit	3.2 in ² (2665 mm ²)
Attachment Configuration	Wedge, plastic
Grinding Segment Dimensions (L x W x H)	2.0 x 0.40 x 0.45 inches (50.8 x 10.2 x 11.4 mm)
Product Dimensions Per Unit (L x W x H)	5.625 x 2.25 x 2.25 inches (142.9 x 57.2 x 57.2 mm)
Product Weight	2.3 lbs (1.0 kg), each

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.