

Surface Preparation Equipment Rotary Asphalt Cutters



FEATURES

- Unitized, welded steel frame
- Patented clamp system
- High capacity, maintenance-free, Timken®-type bearings
- Self-sharpening blade

190C CUT-R-TACH® C SERIES CLAMP MOUNT ATTACHMENT

The C Series CUT-R-TACH Rotary Asphalt Cutting Attachments quickly attach to a wide variety of backhoes, tractor/wheel loaders and similar prime mover vehicles for cutting throughout high density asphaltic materials. Designed to accommodate a wide range of bucket and tooth configurations up to 2-1/2 inches (63 mm) maximum height and 6 inches (153 mm) width. Produces smooth-sided cuts up to 5-1/2 inches (140 mm) deep at rates approaching 6000 lineal feet (1.8 km) per hour. The C Series models each feature a counter-rotating, twin-screw, clamping system that retains the unit tight in both forward and reverse cutting directions. Special, heat-treated, alloy-steel cutting blade is self-sharpening. Quickly field replaced without disturbing bearings or seals. No special installation tools are required for mounting.

SPECIFICATIONS

Frame	Utilized, welded steel plate
Cutting Blade Diameter	19 inches (483 mm)
Hub Assembly	Alloy steel axle with cast hub
Bearings	Timken® type
Mounting	Twin pivoting clamping screws
Maximum Downforce	50,000 lbs (23,000 kg)
Cutting Depth	5-1/2 inches (140 mm)
Weight	245.0 lbs (111.1kg)

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF01111013_v1.1